

PC Board Mountable Pressure Sensor  
 Temperature Compensated  
 0 – 100mV Output  
 Gage, Absolute, Differential  
 Current Excitation

### TO-8 Series

The TO-8 series is a temperature compensated, piezoresistive silicon pressure sensor packaged in a TO-8 configuration.

Integral temperature compensation is provided over a wide temperature range using laser-trimmed resistors. An additional laser-trimmed resistor is included to normalize pressure sensitivity variations by programming the gain of an external differential amplifier.



### FEATURES

- TO-8 Package
- 1.0% Interchangeable Span (provided by gain set resistor)
- Solid State Reliability
- Wide Compensated Temperature Range
- $\pm 0.1$  and  $\pm 0.3$  Pressure Non Linearity

### APPLICATIONS

- Medical Instruments
- Airspeed/Altitude Measurements
- Process Control
- Factory Automation
- Vacuum Measurement
- Handheld Calibrators
- Leak Detection
- Environmental Control
- Level Detection

# TO-8 Series

## Product Definition

Model	Pressure Ranges	Type (G = Gage A = Absolute D = Differential)	Span	Supply Voltage	Current	Compensated Temperature	Unique Feature
<a href="#">13 1psi</a>	0 - 1psi	G	100mV		1.5mA	0°C to 50°C	3/16" Top port
<a href="#">23 1psi</a>	0 - 1psi	G	100mV		1.5mA	0°C to 50°C	1/8" Bottom port
<a href="#">33 1psi</a>	0 - 1psi	D	100mV		1.5mA	0°C to 50°C	3/16" Top port 1/8" Bottom port
<a href="#">43 1psi</a>	0 - 1psi	G	100mV		1.5mA	0°C to 50°C	No port 0.45" Cap
<a href="#">13 Std</a>	0 - 2*, 5, 10, 15, 30, 50 100, 250psi	G, A	100mV		1.5mA	0°C to 50°C	3/16" Top port
<a href="#">23 Std</a>	0 - 2, 5, 10, 15, 30, 50 100, 250psi	G	100mV		1.5mA	0°C to 50°C	1/8" Bottom port
<a href="#">33 Std</a>	0 - 2, 5, 10, 15, 30, 50 100, 250psi	D	100mV		1.5mA	0°C to 50°C	3/16" Top port 1/8" Bottom port
<a href="#">43 Std</a>	0 - 2*, 5, 10, 15, 30, 50 100, 250psi	G, A	100mV		1.5mA	0°C to 50°C	No port 0.45" Cap
<a href="#">17 US</a>	0 - 15, 30, 50, 100, 250psi	G, A	100mV		1.5mA	-20°C to +85°C	UltraStable™ 3/16" Top port
<a href="#">27 US</a>	0 - 15, 30, 50, 100psi	G	100mV		1.5mA	-20°C to +85°C	UltraStable™ 1/8" Bottom port
<a href="#">37 US</a>	0 - 15, 30, 50, 100, 250psi	D	100mV		1.5mA	-20°C to +85°C	UltraStable™ 3/16" Top port 1/8" Bottom port
<a href="#">47 US</a>	0 - 15, 30, 50, 100, 250psi	G, A	100mV		1.5mA	-20°C to +85°C	UltraStable™ No port 0.45" Cap

\* = Gage only

### Canada

Durham Instruments  
900 McKay Road, Unit 3  
Pickering, Ontario  
L1W 3X8  
Tel: 905-839-9960  
1-888-DISENSOR  
Fax: 905-839-4325

Email: [sales@disensors.com](mailto:sales@disensors.com)